### EDMOLIFT PRODUCT DATASHEET













Single Scissor Lift Tables



**BETTER ON EVERY LEVEL** 

### **SPECIFICATION RANGE**

 CAPACITY:
 500 - 10,000KG

 LIFT STROKE:
 600 - 2750MM

 CLOSED HEIGHTS:
 160 - 500MM

 RAISED HEIGHTS:
 760 - 3250MM

 PLATFORM WIDTH:
 700 - 1500MM

 PLATFORM LENGTH:
 900 - 4000MM



Model	Capacity (Kg)	Liftstroke (mm)	Closed Ht (mm)	Raised Ht (mm)	Platform L x W (mm)	Motor (KW)	Weight incl. pack (Kg)	Lifting time (sec)
TR 501	500	600	160	760	900 x 700	0.37	140	12
TA 1000	1000	1300	200	1500	2000 x 800	1.5	300	16
TL 1000	1000	820	180	1000	1300 x 700	0.75	185	15
TL 1000B	1000	820	180	1000	1300 x 800	0.75	190	15
TL 1000H**	1000	930	180	1110	1350 800	0.75	214	15
TL 1000XB	1000	820	180	1000	1300 x 1000	0.75	210	15
TL 1001B	1000	820	180	1000	1200 x 800	0.75	180	15
TM 1000	1000	1100	180	1280	1700 x 700	0.75	260	27
TR 1002	1000	600	160	760	900 x 700	0.37	145	22
TM 1500	1500	1100	230	1330	1700 x 1000	1.5	311	17
TM 1500B	1500	1100	230	1330	1700 x 1200	1.5	337	17
TA 2000	2000	1300	230	1530	2000 x 900	1.5	400	30
TB 2000	2000	1000	220	1220	1500 x 1000	1.5	260	26
TB 2000B	2000	1000	220	1220	1500 x 1200	1.5	280	26

Single scissor mechanism lift tables are our most popular format. Ideal as ergonomic and manual handling solutions and as a base lift for loading bay scissor lifts, split level goods lifts and higher capacity, applications.



Single Scissor Edmo Lift XX **Lift Tables** 



**BETTER ON EVERY LEVEL** 

### SPECIFICATION RANGE

CAPACITY: 500 - 10.000KG 600 - 2750MM LIFT STROKE: CLOSED HEIGHTS: 160 - 500MM RAISED HEIGHTS: 760 - 3250MM DI ATEORM WIDTH: 700 - 1500MM PLATFORM LENGTH: 900 - 4000MM



Model	Capacity (Kg)	Liftstroke (mm)	Closed Ht (mm)	Raised Ht (mm)	Platform L x W (mm)	Motor (KW)	Weight incl. pack (Kg)	Lifting time (sec)
TL 2000	2000	820	200	1020	1300 x 800	1.5	237	17
TL 2000B	2000	820	200	1020	1300 x 1000	1.5	249	17
TL 2000XB	2000	820	200	1020	1300 x 1200	1.5	275	17
TS 2001	2000	1500	250	1750	2200 x 1200	1.5	524	27
TS 2001B	2000	1500	250	1750	2200 x 1500	1.5	598	27
TL 3000	3000	820	250	1070	1300 x 800	1.5	300	26
TM 3000	3000	1100	250	1350	1700 x 900	1.5	386	27
TP 3000	3000	2000	400	2400	3000 x 1500	3	1160	38
TT 3000	3000	1700	300	2000	2500 x 1300	3	705	27
TA 4000	4000	1300	350	1650	2000 x 1200	3	650	27
TS 4000	4000	1500	350	1850	2200 x 1200	3	700	27
TS 4000B	4000	1500	350	1850	2200 x 1500	3	770	27
TX 4000	4000	2750	500	3250	4000 x 1500	3	1930	69
TM 6000*	6000	1100	300	1400	1700 x 900	3	550	32
TP 6000	6000	1600	450	2050	2500 x 1300	3,5	1100	4
TT 6000	6000	1600	450	2050	2500 x 1300	3,5	1100	40
TP 10000	10000	1800	550	2350	3000 x 1500	5,5	2030	36
TT 10000	10000	1500	550	2050	2500 x 1300	6	1550	55

### Double Vertical Amo Lift Scissor Lift Tables

BETTER ON EVERY LEVEL

### **SPECIFICATION RANGE**

CAPACITY: 500 - 3,000KG
LIFT STROKE: 1100 - 4,000MM
CLOSED HEIGHTS: 275 - 700MM
RAISED HEIGHTS: 1375 - 4700MM
PLATFORM WIDTH: 700 - 1500MM
PLATFORM LENGTH: 900 - 3000MM



Model	Capacity (Kg)	Liftstroke (mm)	Closed Ht (mm)	Raised Ht (mm)	Platform L x W (mm)	Motor (KW)	Weight incl. pack (Kg)	Lifting time (sec)
TRD 500	500	1100	275	1375	900 x 700	0.37	185	28
TLD 1000	1000	1600	320	1920	1300 x 800	1.5	230	23
TLD 1000XB	1000	1600	320	1920	1300 x 1000	1.5	250	23
TMD 1500	1500	2200	400	2600	1700 x 1000	1.5	460	46
TSD 1500	1500	3000	450	3450	2200 x 1200	1.5	720	55
TAD 2000	2000	2250	450	2700	2000 X 900	1.5	630	59
TBD 2000	2000	1800	360	2160	1500 X 1000	1.5	425	34
TLD 2000	2000	1600	360	1960	1300 x 800	1.5	325	34
TLD 2000B	2000	1600	360	1960	1300 x 1000	1.5	345	34
TLD 2000XB	2000	1600	360	1960	1300 x 1200	1.5	360	34
TMD 3000*	3000	2200	500	2700	1700 x 900	3	580	50
TPD 3000	3000	4000	700	4700	3000 x 1500	3	2100	80
TTD 3000	3000	3300	600	3900	2500 x 1300	3	1200	60

Double and triple scissor mechanism lift tables provide an increase in lift travel without requiring an increase in platform length. An excellent solution for moving loads between two or more floors.



### Triple & Quattro Edmo Lift Scissor Lift Tables

BETTER ON EVERY LEVEL

### SPECIFICATION RANGE

CAPACITY: 1000 - 3,000KG
LIFT STROKE: 2400 - 6,000MM
CLOSED HEIGHTS: 500 - 1000MM
RAISED HEIGHTS: 2900 - 7000MM
PLATFORM WIDTH: 800 - 1500MM
PLATFORM LENGTH: 1300 - 3000MM



Model	Capacity (Kg)	Liftstroke (mm)	Closed Ht (mm)	Raised Ht (mm)	Platform L x W (mm)	Motor (KW)	Weight incl. pack (Kg)	Lifting time (sec)
TLT 1500	1500	2400	500	2900	1300 x 800	1.5	525	60
TMT 1500	1500	3300	600	3900	1700 x 1000	1.5	580	55
TST 2000	2000	4500	700	5200	2200 x 1200	3	1120	80
TPT 4000	4000	6000	1000	7000	3000 x 1500	5.5	2800	104
TSQ 1000	1000	6000	1000	7000	2200 x 1200	3	1500	80

Double and triple scissor mechanism lift tables provide an increase in lift travel without requiring an increase in platform length. An excellent solution for moving loads between two or more



# Horiztonal Lift Tables

BETTER ON EVERY LEVEL

### SPECIFICATION RANGE

CAPACITY: LIFT STROKE: CLOSED HEIGHTS: RAISED HEIGHTS: DI ATEORM WIDTH. PLATFORM LENGTH: 2600 - 5000MM

2000 - 10.000KG 820 - 1700MM 180 - 350MM 1000 - 2000MM 800 - 1300MM



Model	Capacity (Kg)	Liftstroke (mm)	Closed Ht (mm)	Raised Ht (mm)	Platform L x W (mm)	Motor (KW)	Weight incl. pack (Kg)	Lifting time (sec)
TAH 2000	2000	1300	200	1500	4000 x 800	1.5	600	32
TLH 2000	2000	820	180	1000	2600 x 800	0.75	350	30
TMH 3000	3000	1100	230	1330	3400 x 900	1.5	700	35
TAH 4000	4000	1300	230	1530	4000 x 900	1.5	800	45
TBH 4000	4000	1000	230	1230	3000 x 1000	1.5	490	40
TLH 4000	4000	820	200	1020	2600 x 800	1.5	450	35
TSH 4001	4000	1500	250	1750	4400 x 1200	1.5	1000	55
TLH 6000	6000	820	250	1070	2600 X 800	1.5	560	39
TMH 6000	6000	1100	250	1350	3400 x 900	1.5	740	55
TTH 6000	6000	1700	300	2000	5000 x 1300	3	1400	53
TAH 8000	8000	1300	350	1650	4000 x 1200	3	1300	53
TSH 8000	8000	1500	350	1850	4400 x 1200	3	1360	53
TMH 10000*	10000	1100	300	1400	3400 x 900	3	1100	64



### Low-Profile Scissor Lift Tables

BETTER ON EVERY LEVEL

### **SPECIFICATION RANGE**

CAPACITY: 500 - 2,000KG
LIFT STROKE: 630 - 970MM
CLOSED HEIGHTS: 80 - 100MM
RAISED HEIGHTS: 710 - 1050MM
PLATFORM WIDTH: 600 - 1270MM
PLATFORM LENGTH: 900 - 1500MM



Model	Capacity (Kg)	Liftstroke (mm)	Closed Ht (mm)	Raised Ht (mm)	Platform L x W (mm)	Motor (KW)	Weight incl. pack (Kg)	Lifting time (sec)
TCR 500*	500	630	80	710	900 x 600	0.75	138	9
TCB 600*	600	720	80	800	1500 x 900	0.75	210	13
TCB 600H*	600	970	80	1050	1500 x 900	0.75	210	19
TCL 1000*	1000	820	80	900	1350 x 800	0.75	250	13
TCL 1000B*	1000	820	80	900	1350 x 1000	0.75	275	13
TCL 1000GB*	1000	820	80	900	1350 x 1270	0.75	300	13
TCL 2000	2000	820	100	920	1350 x 800	0.75	325	24
TCL 2000B	2000	820	100	920	1350 x 1000	0.75	355	24
TCL 2000GB*	2000	820	100	920	1350 x 1270	0.75	400	24

Edmolift invented the low profile scissor mechanism! A very low closed height that can be loaded with a shallow ramp, no need for pit installation. Often used to raise pallets to an ergonomic level. The power pack is remote.



### U & E Shaped Amo Lift Low-Profile Lift Tables

BETTER ON EVERY LEVEL

### SPECIFICATION RANGE

CAPACITY: 600 - 2,000KG
LIFT STROKE: 720 - 970MM
CLOSED HEIGHTS: 80 - 100MM
RAISED HEIGHTS: 800 - 1050MM
PLATFORM WIDTH: 900 - 1180MM
PLATFORM LENGTH: 1350 - 1450MM





Model	Capacity (Kg)	Liftstroke (mm)	Closed Ht (mm)	Raised Ht (mm)	Platform L x W (mm)	Motor (KW)	Weight incl. pack (Kg)	Lifting time (sec)
TUB 600*	600	720	80	800	1450 x 900	0.75	250	13
TUB 600H*	600	970	80	1050	1450 x 900	0.75	250	19
TUL 1000*	1000	820	80	900	1350 x 1080	0.75	240	13
TUL 2000*	2000	820	100	920	1350 x 1180	0.75	350	24

### Important Information

Width Between Outer Forks: TUB 600, TUB 600H: Width Between Forks: TUL 1000, TUL 2000, CUB 1000:

Width of Forks: TUB 600, TUB 600H:

Width of Forks: TUL 1000: Width of Forks: TUL 2000:

580mm

585mm

160mm (inc. central fork)

237.5mm

280mm

Designed for use with two-way entry Euro pallets. Raise pallets to a comfortable height an load directly with a pallet truck, no need for a ramp. The power pack is remote.



## U-Shape Lift & Amo Lift XX Tilt Tables (Low- Profile)

**BETTER ON EVERY LEVEL** 

### **SPECIFICATION RANGE**

CAPACITY: 1500KG
LIFT STROKE: 820MM
CLOSED HEIGHTS: 235/6MM
RAISED HEIGHTS: 826MM

PLATFORM WIDTH: 1310/850 - 1730/1270MM

PLATFORM LENGTH: 1380/1200MM



Model	Capacity (Kg)	Liftstroke (mm)	Closed Ht (mm)	Raised H (mm)	It Platform L x W (mm)	Motor (KW)	Weight incl. pack (Kg)	Lifting time (sec)
ALT 1500UE*	1500	820	235/6	826	380/1200 x 1310/8	35 0.75	390	16
ALT 1500U*	1500	820	235/6	826	380/1200 x 1510/1	0! 0.75	410	16
ALT 1500GB*	1500	820	235/6	826	380/1200 x 1730/1	27 0.75	440	16



Platform and U-pallet bed versions are available. The most ergonomic lift table solution, invented by Edmolift. Raise your load to an ergonomic height and then tilt it towards you. No more bending or stretching to reach your load.



Low-Profile Lift Edmo Lift

& Tilt Tables

BETTER ON EVERY LEVEL

### SPECIFICATION RANGE

 CAPACITY:
 750 - 1500KG

 LIFT STROKE:
 550 - 820MM

 CLOSED HEIGHTS:
 220 - 380MM

 RAISED HEIGHTS:
 770 - 1055MM

 PLATFORM WIDTH:
 770 - 1300MM

 PLATFORM LENGTH:
 1000 - 1300MM



Model	Capacity (Kg)	Liftstroke (mm)	Closed Ht (mm)	Raised Ht (mm)	Platform L x W (mm)	Motor (KW)	Weight incl. pack (Kg)	Lifting time (sec)
ALT 750*	750	820	235	1055	1300 x 800	0.75	300	18
ALT 1500	1500	820	235	1055	1300 x 800	0.75	355	16
ART 750*	750	550	235	785	1000 x 1300	0.75	270	18
ART 1500	1500	550	380	930	1000 x 1300	0.75	355	16
ART 1500 GV	1200	550	220	770	1020 x 770	0.75	300	15



### Pallet Lifters Amo Lift with & without tilt

BETTER ON EVERY LEVEL

### **SPECIFICATION RANGE**

CAPACITY: 750 - 1500KG

LIFT STROKE: 880 - 900MM

CLOSED HEIGHTS: 50 - 700MM

RAISED HEIGHTS: 930 - 970M

PLATFORM WIDTH: 840 - 850MM

PLATFORM LENGTH: 1245 - 1250MM





Model	Capacity (Kg)	Liftstroke (mm)	Closed Ht (mm)	Raised Ht (mm)	Platform L x W (mm)	Motor (KW)	Weight incl. pack (Kg)	Lifting time (sec)
TSL 750	750	900	70	970	1245 x 850	0.75	250	13
TSL 1503	1500	880	50	930	1250 x 840	0.75	670	26
Tilting Pal	llet Lifters							
TSLN 750	750	900	70	970	1245 x 850	0.75	275	13
TSLN 1503	1500	880	50	930	1250 x 540	0.75	710	26

No pit, no ramp. Load pallets with a hand pallet truck or stacker. A highly adaptable pallet and box lifter. Tilting versions also available.



Scissor Lift Trolleys

**BETTER ON EVERY LEVEL** 

### **SPECIFICATION RANGE**

CAPACITY: 200 - 1000KG
LIFT STROKE: 600 - 1515MM
CLOSED HEIGHTS: 300 - 450MM
RAISED HEIGHTS: 900 - 1930M
PLATFORM WIDTH: 300 - 800MM
PLATFORM LENGTH: 900MM



Edmo Lift XX

Model	Capacity (Kg)	Liftstroke (mm)	Closed Ht (mm)	Raised Ht (mm)	Platform L x W (mm)	Power	Weight incl. pack (Kg)	Lifting time (sec)
TZD 203	200	1170	450	1620	900 x 600	N/A	85	N/A
TZD 203B	200	1170	450	1620	900 x 600	Battery	100	Max. 6
TZ 303	300	600	320	920	900 x 600	N/A	65	N/A
TZ 503	500	600	320	920	900 x 600	N/A	75	N/A
TZ 503B	500	600	320	920	900 x 600	Battery	90	Max. 5
EZD 500	500	1515	415	1930	900 x 800	Battery	290	Max. 7
EZ 1001B	1000	600	300	900	900 x 300	Battery	190	Max.7



# Lift Trolleys For Servers, Boxes, Reels and Drums

### **SPECIFICATION RANGE**

 CAPACITY:
 85 - 250KG

 LOWERED PLATFORM HEIGHTS:
 300 - 450MM

 RAISED PLATFORM HEIGHTS:
 900 - 1930M

 OVERALL MAST HEIGHTS:
 300 - 800MM



Model	Capacity (Kg)	Lowered Platform Height (mm)	Raised Platform Height (mm)	Overall Mast Height (mm)
WP 85	85	125	1440	1600
WP 85EM	80	125	1760	1930
WP 105	105	130	1345	1600
WP 105EM	100	130	1655	1920
WP 155	155	130	1345	1600
WP 155EM	150	130	1655	1920
WP 205	205	105	1320	1590
WP 250	250	105	1320	1665

### **ADDITIONAL INFORMATION**

These are highly adaptable lift trolleys with multiple attachment options as seen below, Different attachments often mean different capacities so please get in touch with one of our experts who will be able to specify the perfect trolley for your application.











A super lightweight, compact and manoeuvrable solution for lifting, moving and positioning your load. Exceptionally adaptable, can be used with boxes, reels, drums – almost anything can be bandled with an Edmolift Compact Lifter

